

700 SERIES & 895SS

FEATURES

3 to 3.5 GPM
@ 2000 to
3000 PSI
Oil Fired



Stainless-steel coil skin provides extra durability to withstand the elements (790SS & 795SS)

Heater coil carries a 5-year warranty

50-ft. length of high-pressure hose for ease in cleaning around a large area

Adjustable high pressure detergent injection ensures high-pressure sudsing for better cleaning

Model 795SS

Upright, oil fired burner delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil

hotsy®

PRESSURE WASHERS / SINCE 1970

HOT WATER

ELECTRIC

BELT DRIVE

Simple, easy-to-use control panel includes adjustable thermostat with precision safety controls

5 HP, 230V, 1PH electric motor (795SS) comes with thermal overload protection and manual reset

Hotsy-designed Triplex pumps carry a 7-year limited warranty

Convenient hose-reel bracket accepts swivel or stationary reels for ease in hose maneuverability and storage (optional on gas fired models)

Rust-proof, removable, non-contaminating polyethylene fuel tank includes fuel gauge in cap

Pneumatic tires for easy maneuvering

OPTIONS FOR 700 SERIES

8" Oil-Fired Draft Dampener
360° Pivot Reel, 100'
360° Pivot Reel, 200'



MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	PORTABILITY	DIM (LXWXH)	SHIP WT (LBS)
790SS	1.109-612.0	3.0	2000	4	230/1	20	Oil	289,900	HB4025R	Std	37"x28"x45.5"	450
795SS	1.109-039.0	3.5	2000	5	230/1	24	Oil	289,900	HB4025R	Std	37"x28"x45.5"	455
795SS-208	1.109-040.0	3.5	2000	5	208/1	27	Oil	289,900	HB4025R	Std	37"x28"x45.5"	500
895SS	1.109-077.0	3.5	3000	8.2	230/1	36	Oil	289,900	HM3540R.3	Std	37"x28"x45.5"	480

Distributed by:

hotsy®

The Pressure Washer The Pros Use.
EST. 1970

HOTSY.COM

Tel: 800.525.1976

Fax: 888.880.9631

Email: info@hotsy.com

VISIT US ONLINE

Facebook/Instagram [HotsyCleaningSystems](#)

LinkedIn [Hotsy-Corp](#)

Twitter [TheHotsyMan](#)

YouTube [HotsyCleaningSystems](#)

Get Hotsy Email [Bit.ly/GetHotsy](#)

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +10% and in some cases are tighter within +5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

© 2021 Kärcher North America
P/N HOT_700 Effective 06/21